



N°	Description	Application range by width	Application range by height	Part No.
1	Gear variable 0, L=250, 450-550	—	450-550	K1001-02-N03
	Gear variable 1, L=450, 551-750	—	551-750	K1001-04-N03
	Gear variable 2, L=930, 751-1230, 1 ML	—	751-1230	K1001-09-N03
	Gear variable 3, L=1130, 950-1430, 1 ML	—	950-1430	K1001-11-N03
	Gear variable 4, L=1410, 1231-1710, 2 ML	—	1231-1710	K1001-14-N03
	Gear variable 5, L=1610, 1431-1910, 2 ML	—	1431-1910	K1001-16-N03
	Gear variable 6, L=2090, 1911-2390, 3 ML	—	1911-2390	K1001-21-N03
1a	Gear variable 1, L=450, 551-750, backset 7,5 mm.	—	551-750	K1011-04-N03
	Gear variable 2, L=930, 751-1230, 1 ML, backset 7,5 mm.	—	751-1230	K1011-09-N03
	Gear variable 3, L=1130, 950-1430, 1 ML, backset 7,5 mm.	—	950-1430	K1011-11-N03
	Gear variable 4, L=1410, 1231-1710, 2 ML, backset 7,5 mm.	—	1231-1710	K1011-14-N03
	Gear variable 5, L=1610, 1431-1910, 2 ML, backset 7,5 mm.	—	1431-1910	K1011-16-N03
	Gear variable 6, L=2090, 1911-2390, 3 ML, backset 7,5 mm.	—	1911-2390	K1011-21-N03
	2	Corner transmission 150x150	480-1280	450-2390
2a Bottom corner transmission with lifter, Se 150x150		480-1280	450-2390	K2008-00-N03
2b Bottom corner transmission with lifter, 2ML, 150x150		480-1280	450-2390	K2009-00-N03
2c Corner transmission 2 ML, 150x150		480-1280	450-2390	K2002-00-N03
2d Corner transmission, 2 ML, Se		480-1280	450-2390	K2012-00-N03
3	Narrow corner transmission 50x150	380-480	450-2390	K2003-00-N03
		480-680	350-550	
4	Concealed stay arm connecting plate 1 L=530, 480-680, left	480-680	—	K3030-06-L03
	Concealed stay arm connecting plate 1 L=530, 480-680, right	480-680	—	K3030-06-R03
	Concealed stay arm connecting plate 2 L=650, 600-800, left	600-800	—	K3030-07-L03
	Concealed stay arm connecting plate 2 L=650, 600-800, right	600-800	—	K3030-07-R03
	Concealed stay arm connecting plate 3 L=890, 801-1040, left	801-1040	—	K3030-09-L03
	Concealed stay arm connecting plate 3 L=890, 801-1040, right	801-1040	—	K3030-09-R03
	Concealed stay arm connecting plate 4 L=1130, 1041-1280, left	1041-1280	—	K3030-12-L03
	Concealed stay arm connecting plate 4 L=1130, 1041-1280, right	1041-1280	—	K3030-12-R03
4a	Concealed stay arm for timber profile, 13 mm, 480-800, left	480-800	—	A3003-02-L03
	Concealed stay arm for timber profile, 13 mm, 480-800, right	480-800	—	A3003-02-R03
	Concealed stay arm for timber profile, 13 mm, 801-1040, left	801-1040	—	A3003-03-L03
	Concealed stay arm for timber profile, 13 mm, 801-1040, right	801-1040	—	A3003-03-R03
	Concealed stay arm for timber profile, 13 mm, 1041-1280, left	1041-1280	—	A3003-04-L03
	Concealed stay arm for timber profile, 13 mm, 1041-1280, right	1041-1280	—	A3003-04-R03
5	Middle lock L=400, 1 ML	600-1000	600-1000	K4001-04-N03
	Middle lock L=650, 1 ML	850-1250	850-1250	K4001-06-N03
	Middle lock L=720, 1 ML	920-1320	920-1320	K4001-07-N03
	Middle lock L=820, 2 ML	1251-1430	1251-1430	K4001-08-N03
	Middle lock L=1130, 2 ML	—	1251-1730	K4001-11-N03
5a	Middle lock L=400, 1MR + 1 ML	600-1000	600-1000	K4008-04-N03
	Middle lock L=650, 1MR + 1 ML	850-1250	850-1250	K4008-06-N03
	Middle lock L=820, 1MR + 1 ML	1251-1430	1251-1430	K4008-08-N03
	Middle lock L=1130, 1MR + 2 ML	—	1251-1730	K4008-11-N03
6	Middle lock extension 480 mm	—	1710-2210	K4005-05-N03
	Middle lock extension 680 mm	—	2211-2390	K4005-07-N03
7	Standard locking plate for timber profile 13 mm, 24/8	—	—	A7069-13-N03
7a	Locking plate SE for timber profile 13 mm, 24/8	—	—	S6031-13-L/R03
7b	Tilt locking plate Se for timber profile 13 mm, 24/8	—	—	S6033-13-L/R03
8	Standard locking plate for timber profile 13 mm, 30/20	—	—	A7087-13-N03
8a	Locking plate SE for timber profile 13 mm, 30/20	—	—	S6049-13-L/R03
8b	Tilt locking plate Se for timber profile 13 mm, 30/20	—	—	S6050-13-L/R03
9	Lifting plate 13 mm, 24/8	—	751-2390	A6037-13-N03
9a	Lifting plate 13 mm, 30/20	—	751-2390	A6038-13-N03
10	Wrong op. safety device with sash lifter	—	751-2390	A7001-00-N03
11	Concealed bottom hinge for timber profile, 13 mm, left	—	—	A5026-13-L03
	Concealed bottom hinge for timber profile, 13 mm, right	—	—	A5026-13-R03
12	Concealed bottom sash hinge, 13 mm, left	—	—	A5027-13-L03
	Concealed bottom sash hinge, 13 mm, right	—	—	A5027-13-R03
13	Extension lock 240 mm	—	—	K4003-02-N03
13a	Corner transmissions extension lock L=480 mm	—	—	K4010-00-N03

* - with narrow corner transmission

